



2780 Waterfront Pkwy. E. Dr. Suite 200 Indianapolis, IN 46214
Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.
Customer Service and Technical Service can be reached at 1-800-437-3188

Product: **VERSAGEL® M 200**
Revised
HazMat Name: **Non-Regulated**

Product Code: **PEN3600-00-C-DR**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
VISCOSITY @ 25°C	cPs	D2983	13300.00	27700.00	18000.00
SPECIFIC GRAVITY @ 25/25°C		D4052			.8419
COLOR, SAYBOLT		D156	27		30
APPEARANCE, CLEAR		VISUAL	PASS		PASS

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.



2780 Waterfront Pkwy. E. Dr. Suite 200 Indianapolis, IN 46214
Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.
Customer Service and Technical Service can be reached at 1-800-437-3188

Product: **VERSAGEL® M 500**
Revised
HazMat Name: **Non-Regulated**

Product Code: **PEN3620-00-C-DR**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
VISCOSITY @ 25°C, T-C	cPs	D2983	47000.00	57000.00	50178.30
SPECIFIC GRAVITY @ 25/25°C		D4052			.8445
COLOR, SAYBOLT		D156	27		30
APPEARANCE, CLEAR		VISUAL	PASS		PASS

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.



2780 Waterfront Pkwy. E. Dr. Suite 200 Indianapolis, IN 46214
Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.
Customer Service and Technical Service can be reached at 1-800-437-3188

Product: **VERSAGEL® M 750**
Revised
HazMat Name: **Non-Regulated**

Product Code: **PEN3640-00-C-DR**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
VISCOSITY @ 25°C	cPs	D2983	67000.00	83000.00	73203.33
SPECIFIC GRAVITY @ 25/25°C		D4052			.8409
COLOR, SAYBOLT		D156	27		30
APPEARANCE, CLEAR		VISUAL	PASS		PASS

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.



2780 Waterfront Pkwy. E. Dr. Suite 200 Indianapolis, IN 46214
Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.
Customer Service and Technical Service can be reached at 1-800-437-3188

Product: **VERSAGEL® M 1600**
Revised
HazMat Name: **Non-Regulated**

Product Code: **PEN3660-00-C-DR**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
VISCOSITY @ 25°C	cPs	D2983	132000.00	198000.00	177425.00
SPECIFIC GRAVITY @ 25/25°C		D4052			.8398
COLOR, SAYBOLT		D156	27		30
APPEARANCE, CLEAR		VISUAL	PASS		PASS

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.