

INCI Name: Disodium Oleamido MEA Sulfosuccinate

Product Description

Mackanate OM is a very mild, high-foaming sulfosuccinate that is used in personal care applications. When **Mackante OM** is formulated with Alkyl Ether Sulfates, high foaming shampoos and skin care cleansers are produced with significantly reduced irritation potential to both skin and eyes.

Specifications

Appearance @ 25 Deg C	Clear Liquid
Oven Solids, %	33.5 - 36.5
Solids (Moisture Balance), %	34.0 - 36.0
pH (As Is @ 25 Deg C)	5.0 - 7.0
Color Gardner	5 Max
Viscosity @ 25 C,	2000 Max
#2 CD @ 12 DDM CDC	

#3 SP @ 12 RPM, CPS

Infrared Spectrum Matches Standard Specific Gravity @ 25 Deg C 1.103 – 1.113

Typical Properties

Yeast and Mold, CFU/G	10 Max
Gram Negative Bacteria	Absent
Drocomuctive	

Preservative

DMDM Hydantoin 0.4

Actives (MW 551), % 25.0 – 32.0

Principal Uses

Shampoos	5% -10%
Baby Shampoos	5% - 15%
Skin Cleansers	2% - 15%
Liquid Hand Soaps	2% - 10%
Body Cleansers	2% - 15%

Shelf Life

Shelf life 12 months from date of manufacture.

Chemical Structure

$$\begin{array}{c|cccc} CH(CH_2)_7CH_3\\ \parallel\\ CH&O&O&O\\ \parallel&\parallel&\parallel\\ (CH_2)_7C&---NHCH_2CH_2O&---CCHCH_2C&---ONa\\ \parallel&&\parallel\\ &&&&\\ SO_3Na \end{array}$$

Regulatory

Mackanate OM

TSCA:	Listed	Japan:	Not Listed
EU:	Listed	Korea:	Not Listed
Australia:	Listed	New Zea:	Listed
Canada:	Exempt	Philipp:	Listed
China:	Not Listed	Swiss:	Unknown

Storage and Handling

Mackanate OM is subject to hydrolysis. The rate is temperature sensitive, particularly as temperatures above 30°C are encountered. Storage or handling temperatures above 40°C are not recommended and will result in fairly rapid hydrolysis. If this material gets chilled during transport or after being received clear, it may become hazy and some precipitate may form. Gentle warming (at 35 – 40°C) with mixing should return the material to a clear solution. If the material will not return to clear, it should not be used. **Mackanate OM** stock should be consumed quickly to avoid handling problems with thickened or gelled material.

Packaging

Available in bulk, 200 kilogram drums, 450 pound drums, and 2300 pound totes.

WARNING

The information contained in this document is given in good faith and based on our current knowledge. It is only an indication and is in no way binding, notably as regards infringement of or prejudice to third parties through the use of our products.

RHODIA GUARANTEES THAT ITS PRODUCTS COMPLY WITH ITS SALES SPECIFICATIONS.

This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorizations. Users are requested to check that they are in possession of the latest version of the present document and RHODIA is at their disposal to supply any additional information.

PRODUCT INFORMATION N002614 - FEBRUARY 2014

(33) 01 53 56 50 00

(55) 11 37 47 78 86

(65) 62 91 19 21